

LUXURY TOPS

REPLACEMENT PARTS
HANDLE

EDITION 1

Revision 1

TRUCKMAN FITTING INSTRUCTIONS



Please read these instructions carefully. If you have any questions regarding the fitting of this item call 0845 6444704 or email fitting@autostylinguk.com.

Failure to comply with these instructions may affect any warranty considerations




Auto Styling

TRUCKMAN

www.autostylinguk.com

Handle Replacement



- 1 Open the rear door of the hardtop.
- 2 Remove the interior handle from the door.
- 3 Remove the cover from the door.

4 Unscrew the hex head screw from the middle of the swing arm.

5 Pull off the swing arm, taking care that the spring does not fly off.



NEED ADVICE?

Call our experts on 0845 6444704 or email fitting@autostylinguk.com

6 Unscrew the large and the small nuts holding the handle in place.

7 Replace the handle with the new one.



8 Reverse steps 6-4, making sure that the spring does not get in the way of the spring arm and that the actuator works.

9 Reverse steps 3-1 to finish.

Auto Styling
TRUCKMAN

Auto Styling UK Limited,

Unit 4 Narrowboat Way, Hurst Business Park, Brierley Hill, DY5 1UF, UK

Tel: 0845 6444704 Fax: 0845 64445014

Email: fitting@autostylinguk.com

www.autostylinguk.com

Notice

It is important that safety warnings in the instructions are adhered to.

Do not attempt to fit this product if you are not competent to do so. Improper fitting may affect your warranty considerations. For your safety, we recommend that any wiring is performed by qualified Auto Electricians.

Due to tolerances of the vehicle fitting of this product may differ from the exact fitting specifications described in the instructions. It is the responsibility of the fitter that the product is installed correctly.

Fitting instruction revisions may be found at www.autostylinguk.com